



TECHNICAL DATA

MASSES

Max. operating mass	500 kg
Transport mass	220 kg

DIMENSIONS

Length, max	2000 mm
Transport dimensions (LxWxH)	1670 x 1000 x 1100 mm
Working width, max.	1000 mm
Working width, min.	250 mm

MATERIAL HOPPER

Capacity	150 l
----------	-------

TRACTION

Max. working speed	30 m/min
Transport speed, max	3.5 km/h

ENGINE

Manufacturer/Model	Honda GXV 160
Emissions according to	EPA
Rated power	3.2 kW
Type	Air cooled gasoline
Number of cylinders	1
Fuel tank capacity	5 l

DRIVE SYSTEM

Drive system	Hydrostatic
--------------	-------------

UNDERCARRIAGE

Front wheels	2x hydrostatically driven wheels, 400 mm diameter
Rear wheels	1x swivel castor wheel, 260 mm diameter

STANDARD FEATURES

- Two hydrostatically driven wheels and a swivel castor wheel
- Forward and reverse drive controls at operator handle
- Layer thickness control with independent left and right hydraulic cylinders
- Operating width control with hydraulically controlled hatches
- Screed heated with exhaust gas recovery
- Hopper container
- Parking brake

Find us locally at www.dynapac.com

We reserve the right to change specifications without notice. Photos and illustrations do not always show standard versions of machines. The above information is a general description only, all informations are supplied without liability.